



RAPTOR COLOR

Safety Data Sheet RCOL-US-SDS

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 11/15/2017

Revision date: 01/07/2019

Supersedes: 01/07/2019

Version: 1.2

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : RAPTOR COLOR
 UP Number : UP4854, UP4855, UP4856, UP4857, UP4858, UP4859, UP4860, UP4861, UP4862, UP4863, UP4864, UP4865, UP4866, UP4867, UP4868, UP5031, UP5032, UP5033, UP5034, UP5035, UP5036, UP5037, UP5038, UP5040
 Other means of identification : Component of UP5054, UP5055, UP5056, UP5057, UP5058, UP5059, UP5060, UP5061, UP5062, UP5063, UP5064, UP5065, UP5066, UP5067 and UP5068

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coatings and paints, thinners, paint removers
 Recommended use : Coating

1.3. Supplier

U-POL US Inc
 108 Commerce Way
 Easton, PA 18040 - United States
 T 1-800-340-7824 - F 1-800-787-5150
technicalsupport@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3 Flammable liquid and vapor

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
 Hazard statements (GHS US) : Flammable liquid and vapor
 Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Keep container tightly closed.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Wear protective gloves, protective clothing, eye protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 In case of fire: Use dry sand, extinguishing powder, foam to extinguish.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

2.4. Unknown acute toxicity (GHS US)

RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
n-butyl acetate	(CAS-No.) 123-86-4	5 – 23	Flam. Liq. 3, H226 STOT SE 3, H336
carbon black	(CAS-No.) 1333-86-4	< 5	Carc. 2, H351

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Reactivity : Flammable liquid and vapor.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.

RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-butyl acetate (123-86-4)		
ACGIH	Local name	n-Butyl acetate
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	ACGIH OEL STEL [ppm]	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	710 mg/m ³
OSHA	OSHA PEL (TWA) [2]	150 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
carbon black (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH OEL TWA	3 mg/m ³ (Inhalable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2021
OSHA	OSHA PEL (TWA) [1]	3.5 mg/m ³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Various
Odor	: strong
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 38 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.3 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
No data available	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

As Packaged Regulatory VOC	: 330 g/l (2.75 lb/gal)
As Packaged Actual VOC	: 330 g/l (2.75 lb/gal)

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
-----------------------	------------------

RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
ATE US (oral)	10760 mg/kg body weight
ATE US (dermal)	14112 mg/kg body weight
ATE US (gases)	390 ppmV/4h

carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 4.6 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (dust))

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

carbon black (1333-86-4)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance

RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-butyl acetate (123-86-4)	
BOD (% of ThOD)	0.46
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

n-butyl acetate (123-86-4)	
BCF - Fish [1]	15.3 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

n-butyl acetate (123-86-4)	
Surface tension	0.0163 N/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.
carbon black (1333-86-4)	
Surface tension	Not applicable (solid)
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.

12.5. Other adverse effects

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN1263 Paint, 3, III
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242

RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 367 - For the purposes of documentation and package marking: a. The proper shipping name "Paint related material" may be used for consignments of packages containing "Paint" and "Paint related material" in the same package; b. The proper shipping name "Paint related material, corrosive, flammable" may be used for consignments of packages containing "Paint, corrosive, flammable" and "Paint related material, corrosive, flammable" in the same package; c. The proper shipping name "Paint related material, flammable, corrosive" may be used for consignments of packages containing "Paint, flammable, corrosive" and "Paint related material, flammable, corrosive" in the same package; and d. The proper shipping name "Printing ink related material" may be used for consignments of packages containing "Printing ink" and "Printing ink related material" in the same package. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

Transportation of Dangerous Goods

Transport document description (TDG)	: UN1263 PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) with not more than 20 per cent nitrocellulose by mass if the nitrogen content of the nitrocellulose is not more than 12.6 per cent by mass), 3, III
UN-No. (TDG)	: UN1263
Proper Shipping Name (TDG)	: PAINT
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Packing group (TDG)	: III - Minor Danger
TDG Special Provisions	: 59 - Substances that are listed by name in Schedule 1 must not be transported under this shipping name. Substances transported under this shipping name may contain not more than 20% nitrocellulose if the nitrocellulose contains not more than 12.6% nitrogen (by dry mass), 142 - The following shipping names may be used to meet the requirements of Part 3 (Documentation) and Part 4 (Dangerous Goods Safety Marks) when these dangerous goods are offered for transport in the same means of containment: (a) "PAINT RELATED MATERIAL" may be used for a means of containment containing both paint and paint related material; (b) "PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE" may be used for a means of containment containing both paint, corrosive, flammable, and paint related material, corrosive, flammable; (c) "PAINT RELATED MATERIAL, FLAMMABLE, CORROSIVE" may be used for a means of containment containing both paint, flammable, corrosive, and paint related material, flammable, corrosive; and (d) "PRINTING INK RELATED MATERIAL" may be used for a means of containment containing both printing ink and printing ink related material.
Explosive Limit and Limited Quantity Index	: 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L

RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

Transport document description (IMDG)	: UN 1263 PAINT, 3, III
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

Air transport

Transport document description (IATA)	: UN 1263 Paint, 3, III
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

n-butyl acetate	CAS-No. 123-86-4	5 – 23%
carbon black	CAS-No. 1333-86-4	< 5%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

n-butyl acetate (123-86-4)	
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

n-butyl acetate (123-86-4)	
Listed on the Canadian DSL (Domestic Substances List)	
carbon black (1333-86-4)	
Listed on the Canadian DSL (Domestic Substances List)	


EU-Regulations

No additional information available

National regulations

carbon black (1333-86-4)	
Listed on IARC (International Agency for Research on Cancer)	

15.3. US State regulations

 **WARNING:** This product can expose you to carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
carbon black(1333-86-4)	X					

RAPTOR COLOR

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
n-butyl acetate(123-86-4)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
carbon black(1333-86-4)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 01/07/2019

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



SDS US GHS (GHS HazCom2012)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.